

Smart Version of AC Charger

22KW/11KW/7KW



 TUV certification

 DLB & Solar charging

 Multiple security protections

 Fast charging
22KW/ 11KW/7KW

 Full chain encryption

 Long-term use
of 100,000 times

 WiFi & Bluetooth
4G/Ethernet

 Type A+DC6mA
(TUV RCD+RCCB)

 Mobile APP control
RFID, plug&play

 Easy installation
& maintenance

 IP55, IK10

 OCPP, OTA
Smart scheduled charging

SPECIFICATION

AC Power supply	EAW-A007xxx	1P + N + PE
	EAW-A011xxx,EAW-A022xxx	3P + N + PE
Rated Power	EAW-A007xxx	7.4kW
	EAW-A011xxx	11kW
	EAW-A022xxx	22kW
Rated Voltage	EAW-A007xxx	AC 230V, 50/60Hz
	EAW-A011xxx,EAW-A022xxx	AC 400V, 50/60Hz
Rated Current	EAW-A011xxx	16A
	EAW-A007xxx,EAW-A022xxx	32A
Charge Mode	Type2 IEC 62196-2	
Sockets/ Plugs	EAW-A0xxSxx	Socket, Case B connection
	EAW-A0xxTxx	Cable(5m), Case C connection
Charging Control	Smart phone APP control, Tap card control, Plug-and-charge	
Display Screen	EAW-A0xxx1x	3.8-inch LCD screen
Indicator Light	EAW-A0xxx0x	4 LED lights
Communication Interface	WiFi/BT, 4G, LAN	
Communication Protocol	OCPP 1.6j	
Safety Protection	Over current protection, over voltage protection, under voltage protection, over temperature protection, leakage protection, unconnected PE ground protection etc	
RCD	Type A+DC6mA(TUV RCD+RCCB)	
Altitude	2000m	
IP Code	IP55	
Storage temperature	-40~75°C	
Operation temperature	-30-50°C	
Relative humidity	95%RH, No water droplet condensation	
Vibration	0.5G, No acute vibration and impaction	
Installation location	Indoor or outdoor, good ventilation, no flammable, explosive gases	
Product Weight (NW)	EAW-A022Sxx	2.6KG
	EAW-A011Sxx	2.4KG
	EAW-A007Sxx	2.4KG
	EAW-A022Txx	5KG
	EAW-A011Txx	3.8KG
	EAW-A007Txx	4KG
Dimension	EAW-A0xxSxx	Height: 455 mm Width: 260 mm Depth: 150mm
	EAW-A0xxTxx	Height: 455 mm Width: 260 mm Depth: 230mm
Mounting	Wall-mounted or pole-mounted (mounting pole is optional)	